

ArChine Slideway HP 68

Product Description

Archine slideway HP 68 is a special demulsifying lubricant for machine tool slideways and guides.

Application

Archine slideway HP 68 is suitable for the latest NC and CNC machines and flexible processing centres where high positioning accuracy is required to achieve top levels of surface finish and component tolerances.

Due to its substantial adhesiveness and good demulsifying behaviour a premature washing off of **Archine slideway HP 68** by the circulating emulsion is avoided. Therefore, slideways and guides are well protected against corrosion and swelling of plastic coatings is also avoided, respectively.

The good demulsifying properties of **Archine slideway HP 68** makes sure that only small amounts of tramp oil enter the emulsion which can easily be separated. Therefore, circulating emulsions remain stable for a longer period of time and disturbing effects on the working process and the operator are clearly reduced.

Typical Data

Item	Test Result
Density (20°C) g/cm ³	0.859
Viscosity 40°C mm ² /s	67.8
Viscosity 100°C mm ² /s	8.7
Pour point, °C	-27°C

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com

ARCHINE

Shanghai PingYiao Trading CO., Ltd.

Foam stability	20/0 10/0 20/0
Copper Corrosive test 100℃, 3h	1
Flash poin / °C	243℃
Water %	Trace
Viscosity index	100

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com