

ArChine Comptek FPC 32**Food Grade Compressor Oil**

NSF Registration No. 147703 Place of Origin: Shanghai,China

GENERAL:

ArChine Comptek FPC 32 is custom-blended with synthetic base fluids and special additives to provide excellent protection against wear and outstanding cold-temperature fluidity. It offers excellent performance in a wide range of temperatures including sub-zero temperatures. It also offers excellent water separation as well as rust, corrosion, deposit and water-washout resistance to protect components. In addition, it resists fling-off and is designed to remain on the chain for maximum lubrication and protection.

ArChine Comptek FPC 32 is long life lubricant and recommended for use in screw compressors, evaporators and spiral freezers operating at extremely low temperatures including cryogenic-freezing temperatures.

ArChine Comptek FPC 32 meets USDA H-1 requirements for incidental food contact and complies with requirements for FDA 21 CFR 178.3570.

ATTRIBUTES

- Very high viscosity index for enhanced lubrication and superior protection at low temperatures
- Excellent film strength and anti-wear properties
- Outstanding cold-temperature fluidity
- Resists fling-off and remains on the chain for maximum lubrication and protection
- High stability and demulsibility in wet environments
- Excellent rust, corrosion and deposit resistance
- Non-toxic/non-hazardous

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road,Xuhui District , Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com

Applications

The following types of compressor applications have shown excellent performance with the ArChine Comptek FPC 32 oil:

- Primarily recommended for rotary screw and vane air compressor
- Very effective in screw type compressors with oil injection cooling
- Units operating under severe conditions
- Multistage units with a history of excessive oil degradation from mineral oil-based products
- Compressor systems with critical gears and bearings
- Compressors used in stationary and mobile applications
- For spiral freezers operating at extremely low temperatures including cryogenic-freezing temperatures

TYPICAL PROPERTIES*:

| Items | ArChine Comptek FPC 46 |
|--|----------------------------|
| Appearance | Yellow, transparent liquid |
| Density@ 20°C, g/cm ³ | 0.838 |
| Viscosity @ 40°C, mm ² /s | 30.5 |
| Viscosity @ 100°C, mm ² /s | 5.53 |
| Viscosity Index | 120 |
| Pour Point, °C | -51 |
| Flash Point, °C (open cup) | 232 |
| Foaming 24°C, 93.5°C, after 24°C | 10/0 20/0 10/0 |
| Copper corrosion, 100°C/3hr, grade | 1b |

*Typical data shall not be used as product specifications.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com

ARCHINE

Shanghai PingYiao Trading CO., Ltd.

Shanghai PingYiao Trading CO., Ltd.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com