

## **ArChine Vacumtek FPV 150**

### **Synthetic Food Grade Vacuum Pump Oil**

#### **Product Description**

ArChine Vacumtek FPV 150 is custom-blended polyalphaolefin (PAO) synthetic fluid. The product is giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

ArChine Vacumtek FPV 150 is long life lubricant formulated with rust and oxidation inhibitors. It provides high viscosity index, high flash point, low pour point and excellent hydrolytic stability. The high thermal and oxidation stability reduces the formation of oxidation byproducts and acidic materials which eventually cause deposits and varnish.

#### **Features and Benefit**

- Less frictional drag
- Less down time
- Lower equipment maintenance
- Good demulsibility
- Sufficient low vapour pressure
- Reduced oil consumption

#### **Applications**

ArChine Vacumtek FPV 150 can be recommended for use in rotary and slide vane vacuum pumps.

ArChine Vacumtek FPV 150 is NSF H-1 registered for use in federally inspected meat and poultry plants. Complies with FDA 21 CFR 178.3570 Lubricants with incidental food contact.

#### **Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd.

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai 200235 P.R.China

Telephone helpline: (86)15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)

**Typical Properties\***

ArChine Vacumtek FPV	ISO 150
Appearance	Light yellow transparent liquid
Density@ 20°C, g/cm <sup>3</sup>	0.849
Viscosity@ 40°C, mm <sup>2</sup> /s	144.6
Viscosity@ 100°C, mm <sup>2</sup> /s	13.46
Viscosity Index	142
Flash Point, °C (open cup)	244
Fire point, °C	266
Pour Point, °C	-45
Foaming Characteristics	
24°C,	10/0
93.5°C,	5/0
24°C	10/0
Copper Strip Corrosion, 100°C/3hr, grade	1
NSF Registration number	150935

\*Typical data shall not be used as product specifications.

**Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd.

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai  
200235 P.R.China

Telephone helpline: (86)15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)