

# Shanghai PingYiao Trading CO., Ltd.

#### **ArChine Silicona FMO 680**

### **Food Grade Dimethyl Silicone Oil**

Approved by NSF HT1, 3H, H1, NSF Registration No. 148509

## **Description**

Food Grade Dimethyl Silicone Oil ArChine Silicona FMO is a series of products with viscosity of 1~2000,000 cst. Under strict production process, the quality of the ArChine Silicona FMO is able to reach the standard of food, cosmetics and pharmaceutical usage.

## **Technical Index**

Туре	ArChine Silicona FMO 680
Viscosity(25°C) cst	680±10%
Flash Point °C, ≥	320
Freezing Point°C, <	-47
Density (25°C) g/cm <sup>3</sup>	0.966~0.974
Volatile Content(150°C, 3h)% ≤	0.8
Viscosity Temperature Coefficient	0.58~0.62
Refractive Index (25°C)	1.4020~1.4053
Dielectric Constant (25°C,50Hz)	2.72~2.78
Thermal Conductivity W/(m.K)	0.1590

#### **Features**

#### **Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: <a href="https://www.pingyiao.com">www.pingyiao.com</a> E-mail: <a href="mailto:info@pingyiao.com">info@pingyiao.com</a>



# Shanghai PingYiao Trading CO., Ltd.

- Excellent resistance to high and low temperatures
- Special lubricity, smoothness and softness.
- Excellent chemical stability and electrical insulating property.
- Good hydrophobic and moisture resistance property.
- Low surface tension and thermal rate.

## **Application**

- Used in production of skin creams, bath gel, shampoo and other cosmetics.
- Used as additives and agents in production of rubber, plastic, latex, polyurethane etc.
- Used as defoaming agent, lubricant, release agent in pharmaceutical, food, chemical, paint, building materials and other industries.
- Used as high-grade lubricants, liquid springs, cutting fluids, buffers oil, transformer oil, high temperature brake fluid, brake fluid, instrument damping oil, mold release agent in machinery, automotive, instrumentation, electronics and other industries.
- Used as softener, water-repellent agents, feel modifiers and lubricants for sewing line, chemical fiber spinneret in textile, apparel and leather industry.

# **Packing**

200KGS Iron drums or 1000KGS IBC drums.

# Storage

- 1. Required sealed and airproof packing.
- 2. The product should be stored in a shady cool, ventilated warehouse.
- 3. Keep away from fire, heat source, direct sunlight and rain.
- 4. Avoid from oxidant, acid, alkali chemical materials and other impurities.

#### **Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com



## Shanghai PingYiao Trading CO., Ltd.

5. Transportation: As non-dangerous chemicals.

Shandhai Ping Yiao Trading Co.

#### **Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com

<sup>\*</sup>Typical data shall not be used as product specifications.