

**ArChine Foodrance WSI 2 PTFE**

Grease with PTFE Appropriated for Incidental Contact with Foodstuffs

**NSF Registration No. : 145484**

**Place of Origin: France**

NLGI Grade	2
Color	White
Appearance	Smooth
Penetration at 25°C (0.1mm)	
worked 60 strokes	265-295
worked 10,000 strokes	285-315
Dropping point	none
Soap	Inorganic
Temperature of use, °C	-20 ~ 180

**PROPERTIES**

- Lubricating performances reinforced by the addition of additives which improve the rubbing coefficient.
- Removal of jamming in corrosive environment.
- Insoluble in water and vapour.
- It is essential where it is necessary to eliminate jerks.
- NSF H1, Halal and Kosher approved.

ArChine Foodrance WSI 2 PTFE also assures:

- An exterior protection against the oxidation.
- An excellent resistance at high temperatures.

### **USES**

They are multiple in the food-processing sector:

- Open gears or not waterproof gearboxes
- Crimpers in canning factories.
- Bearings of oven trolleys.
- Safety valves situated next to foodstuffs.
- Pump pistons needing grease (Bottling factories, sweets, yoghurts and cakes factories).
- Conveyors chains.
- Slides with hooks
- General greasing of equipment, joints, various motions; where it is recommended to use grease next to foodstuffs.

\*Typical data shall not be used as product specifications.