

## CP-9026-100

CP-9026-100 is a custom-blended severely hydrocracked isodewaxed lubricant.

Primary benefits include:

Extended 4,000-5,000 typical life

Very low deposit formation for extended valve life

Non-toxic and non-hazardous

Excellent wear protection

This high-performance lubricant is recommended for use in:

Reciprocating air compressors

### TYPICAL PROPERTIES\*\*

### CP-9026-100

Viscosity @ 40°C, cSt, ASTM D445	109
Viscosity @ 100°C, cSt	11.3
Viscosity @ 100°F, SUS	527
Viscosity @ 210°F, SUS	65
Viscosity Index ASTM D2270	89
Density, lb/gal, 60°F, ASTM D4052	7.25
Pour Point °F (°C) ASTM D97	-12(10)
Flash Point, C.O.C., °F (°C) ASTM D92	510(266)
Fire Point, C.O.C., °F (°C) ASTM D92	575(302)
Specific Gravity, ASTM D4052	0.869

\*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Tel: 86-21-64705533

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: [www.pingyiao.com](http://www.pingyiao.com)