

ArChine Arclith MP 3A

ArChine Arclith MP 3A is lithium refined mineral oil grease. And it contains anti-oxidation additives and rust-inhibiting additive.

Properties

High thermal resistance, extremely water resistance, mechanical stability, corrosion resistant, resistant to oxidation;

This product can substitute for calcium-soap grease and sodium soap grease.

Application

ArChine Arclith MP 3A suits for lubrication of roller and friction bearings and other parts of common mechanical equipment.

Operating temperature for long-term lubrication: $-20^{\circ}\text{C} \sim 100^{\circ}\text{C}$

Technical Data

TEST ITEMS	UNIT	METHOD
Worked penetration after 60 strokes 0.1mm	220-250	GB/T 269
Copper Strip Test (T ₂ Copper, 100°C, 24h)	Copper no black and green change	GB/T 7326
Water loss (38°C, 1h), %	≤ 8	SH/T 0109
Evaporation capacity (99°C, 22h), %	≤ 2.0	GB/T 7325
Oxidation stability, pressure drop, Mpa (99°C, 100h, 0.760Mpa)	≤ 0.070	SH/T 0325
Bleeding test (100°C, 24h), %	≤ 5	SH/T 0324
Mechanical admixture $\geq 10\mu\text{m}$	≤ 5000	SH/T 0336

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com

$\geq 25\mu\text{m}$ $\geq 75\mu\text{m}$ $\geq 125\mu\text{m}$	≤ 3000 ≤ 500 ≤ 0	
Extended worked penetration (100,000 strokes), 0.1mm	≤ 320	GB/T 269
Corrosion preventive properties (52°C, 48h)	≤ 1	GB/T 5018

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com