

LOSOID 58430/T-20

Introduction:

LOSIMOL Special Lubricants have for decades been a well-known name in the optical and precession-mechanical industries. Where lubricants with specific properties such as: retarding power, ductility,low evaporation loss f. i. are needed in order to meet particular requirements, well-known.LOSIMOL products are used again and again.

LOSIMOL strong point lies in producing lubricants which result in either sticking effect (such as in the focusing devices of binoculars, in the heads of cine tripods, etc.)or a smooth motion in slowacting mechanism (such as in the rotation of objective lenses and oculars etc.). In addition, many of our lubricants possess noise-damping which are important in projectors, audio equipment, etc. The more exactly you can describe a particular problem, the more ecisely we can propose solutions to it.

General Technical Data Regarding LOSOID 58420/T-20:

Penetration Worked(Consistency)	abt.280/300
Apparent Dynamic Viscosity mp a.s(cp)	abt.20.000cp
Ductility	good
Evaporation Loss	below 0.3% - 16h/70°C
Spreading Behaviour	Sp = 21/70 °C
Operating Temperature Range	abt30°C/+125°C
Resistant Plastics	PA PC POM PS SAN ABS

Shanghai PingYiao Trading CO., Ltd.Tel: 86-21-64705533Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250Telephone helpline: 15900706965Fax: 86-21-64705533-209Website: www.pingyiao.comE-mail: info@pingyiao.com