

LOSOID CRL 50090**Introduction**

The lubricant described in this data sheet belongs to the LOSIMOL LOSOID Series. Especially developed for the requirements of the cleanroom technology (e.g. semiconductor manufacturing). This means that the cleanroom lubricants not only correspond to usual tribological characteristics but also to the specific requirements of cleanroom technology like number and size of particles. Therefore LOSIMOL Cleanroom Lubricants are classified according to these two items.

Cleanroom Characteristics

The determination of the results of the particle emission behaviour and particle size distribution has been done under standardised conditions. A wafer positioning unit of a semiconductor inspection equipment served as a test stand.

General Technical Data Regarding LOSOID CRL 50090:

Penetration Worked(Consistency)	310/330
Apparent Dynamic Viscosity mp a.s(cp)	abt. 13.000cp
Ductility	fair
Evaporation Loss	0.3% - 16h/70°C
Spreading Behaviour	Sp = 45/70°C
Operating Temperature Range	abt. -20°C/+85°C
Resistant Plastics	PA, PPO, POM

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com