

ArChine Arcplex HTB 200

Introduction:

The product is made of new synthetic complex soap thickener and joined the refined multi-effect additives.

Property:

Excellent high temperature performance, difficultly lost in the lubrication area.

Good extreme pressure performance, provides effective lubrication for the bearing parts.

Good water resistance, lubrication equipment for wet environment.

Good rubber adaptability, compatibility with most of the rubber.

Excellent colloidal stability, long-term storage and not easy point oil.

Application:

The product is designed specifically for aviation lubrication, but also for a variety of civil lubrication. Apply to aircraft stabilizer bearing, control, landing gear, wheel systems, aviation electronics, generators and petrochemical, textile and other various industries, the import, domestic devices, high-speed, wide temperature range of the various bearing lubrication.

Compared to mineral oil, the lubrication cycles of equipment may be extended 10 to 15 times.

Operating Temperature Range: -50°C ~ 200°C

Technical Data:

Items	Technical Data	Method
Appearance	Pale smooth uniform ointment	Visual
Drop point, °C	330	GB/T 3498
1/4 Worked Penetration, 0.1mm	60	GB/T 269

Distributor Wanted**Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com

ARCHINE

Shanghai PingYiao Trading CO., Ltd.

Pressure Oil Separation, %	3.0	GB/T 392
Evaporation Capacity(180°C), %	2.0	SH/T 0337
Corrosion Test (No.45 Steel, 100°C, 3h)	Qualified	SH/T 0331

Shanghai PingYiao Trading CO., Ltd.

Distributor Wanted

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com