

ArChine Switch HTG 200

Introduction:

The products use inorganic thickener and add a fine conductive material, anti-corrosion additives and oil agent to refine by a special process.

Property:

Reduce resistance of the contact points. Improve electrical conductivity.

Keep long-lasting lubrication.

Good compatibility with plastics, Also a stable aging.

Containing anti-wear agent, Prolonged the use of time of the system switch.

Application:

For lubrication of the metal switch contact points of electronics or electrical products. Such as the ignition switch, turn switch contact sports sites in automobile industry.

Operating Temperature Range: -30℃ ~ 200℃

Technical Data:

Items	Technical data	Method
Appearance	white uniform ointment	Visual
Worked Penetration, 0.1mm	280	GB/T 269
Drip point, °C	320	GB/T 3498
Corrosion (T ₂ Copper, 100℃, 24h)	Copper no green or black change	GB/T 7326 Second method
Water Loss (38℃, 1h) ,%	1.25	SH/T 0109

Distributor Wanted

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com

Shanghai PingYiao Trading CO., Ltd.

Distributor Wanted

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com