ArChine Arcsyn HTG 180

Application

ArChine Arcsyn HTG 180 is recommended for use in Anti Friction and Plain Bearings. Also in threaded spindles, gears, worms and similar parts exposed to high pressure and extreme temperatures. Extremely well suited for a wide temperature range, high loads, vibrations, high speed and open air conditions.

Advantages and Benefits

- 1. High efficiency even under the impact of water.
- 2. Best use under extreme stress.
- 3. Economic because of low-wear operation and long re-lubrication intervals
- 4. Manifold application in areas beyond the performance of normal greases.

Technical Data

Appearance	Light Beige
Thickener	Barium Complex soap
Base Oil	Synthetic oil
Consistency	NLGI grade 2 DIN 51 818
Worked Penetration	265 -295 0.1 mm DIN ISO 2137
Drop Point	approx. +230°C DIN ISO 2176
Base Oil Viscosity	50 cSt +40°C DIN 51 562
	8 cSt +100°C DIN 51 562
Temperature Range	- 40°C to +180°C
Water Resistance	Rating: 0 - 90 DIN 51 807
DN Factor	approx. 800,000

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250 Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

Mode of Application

Cleaning of previously used greases in necessary

In Anti friction bearings, the instructions issued by the bearing manufacturer must be followed.

al lubrica.

Litch

Tradition

Shanghai Pingeriae

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com