

ArChine Synchron POE 2000U

Fully synthetic high temperature chain lubricants

DESCRIPTION

ArChine Synchron POE 2000U product is synthetic POE high temperature lubricants designed primarily for high temperature equipment, such as oven chains and tenter frame ovens, as well as paint and ceramic curing ovens. Satisfactory performance can also be expected in applications involving bearing lubrication. Formulated from a quality synthetic base stock and additive system, ArChine Synchron POE 2000U has better oxidation stability and lower ash residue compared with general synthetic ester lubricant, it also provides the following performance benefits.

- Excellent high temperature oxidation and thermal stability for prolonged lubricant life.
- Extremely low volatility resulting in less oil consumption.
- Superior antiwear properties for reduced chain drag.
- Does not form carbon residue as petroleum products do.
- Very few ash residue, maintain a clean operating environment for frame rails and chains.

TYPICAL PROPERTIES

Appearance	Yellow clear liquid
Viscosity@40°C, cSt	2204.76
Viscosity@100°C, cSt	195.66
Viscosity index	214
Density@20°C, g/cm ³	0.996
Flash point, °C	272
Fire point, °C	302
Pour point, °C	-21
Copper corrosion, 3h/100°C	1b

These technical data are based on average test results. Minor deviations may occur from case to case.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai 200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com