

ArChine Synchron POE 280**Fully synthetic high temperature chain lubricants****DESCRIPTION**

ArChine Synchron POE 280 product is synthetic POE high temperature lubricants designed primarily for high temperature equipment, such as oven chains and tenter frame ovens, as well as paint and ceramic curing ovens. Satisfactory performance can also be expected in applications involving bearing lubrication. Formulated from a quality synthetic base stock and additive system, ArChine Synchron POE 280 provides the following performance benefits.

- Excellent high temperature oxidation and thermal stability for prolonged lubricant life
- Extremely low volatility resulting in less oil consumption
- Superior antiwear properties for reduced chain drag
- Does not form carbon residue as petroleum products do
- Maintain a clean operating environment for frame rails and chains

TYPICAL PROPERTIES

Appearance	Yellow
Viscosity @40°C, cSt	300.5
Viscosity @100°C, cSt	36.5
Viscosity index	170
Density@ 20°C, g/cm ³	0.984
Flash point, °C	278
Pour point, °C	-39
Total acid number, mg KOH/g	1.02
Copper corrosion, 3h/100°C	1b
RBOT@150°C, min	1975
Noack@250°C, 60min, %	1.1

These technical data are based on average test results. Minor deviations may occur from case to case.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com