## **GB-8886-150 PAG Synthetic Refrigeration Compressor Oil**

GB-8886-150 is unique co-polymers of polyalkylene glycols (PAG). The synthetic base oil ensures good cold flow properties, a high chemical stability and low tendency to evaporation. Primary benefits include:

- Low maintenance costs due to extended oil change intervals and reduced oil consumption
- High efficiency of the refrigerating plants
- Low operating costs due to long service life of filters and oil separators

This high-performance lubricant is recommended for use in:

## **Typical Physical Properties\***

Automotive Air Conditioning Applications	
<b>Typical Physical Properties*</b>	XINE
Appearance	Colorless transparent liquid
Density@20°C, g/cm <sup>3</sup>	1.040
Viscosity@40°C, mm <sup>2</sup> /s	149.1
Viscosity@100°C, mm <sup>2</sup> /s	27.77
Viscosity Index	225
Flash Point(open cup),	248
Fire Point, °C	268
Pour Point, ℃	-42
Copper Strip Test, 100°C, 3hr	1
Foaming, 24°C	30/0

\*The above data is typical data, not as product specifications.

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai 200235 P.R.China Fax: 86-21-64705533-209 Telephone helpline: (86)15900706965 Website: www.pingyiao.com E-mail: info@pingyiao.com