

GB-8886-68 PAG Synthetic Refrigeration Compressor Oil

GB-8886-68 is unique co-polymers of polyalkylene glycols (PAG). The synthetic base oil ensures good cold flow properties, a high chemical stability and low tendency to evaporation. Primary benefits include:

- Low maintenance costs due to extended oil change intervals and reduced oil consumption
- High efficiency of the refrigerating plants
- Low operating costs due to long service life of filters and oil separators

This high-performance lubricant is recommended for use in:

- Automotive Air Conditioning Applications

Typical Physical Properties*

Appearance	Colorless transparent liquid
Density@20°C, g/cm ³	1.032
Viscosity@40°C, mm ² /s	68.8
Viscosity@100°C, mm ² /s	13.99
Viscosity Index	212
Flash Point(open cup), °C	228
Fire Point, °C	248
Pour Point, °C	-48
Copper Strip Test, 100°C, 3hr	1
Foaming, 24°C	25/0

*The above data is typical data, not as product specifications.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yinhai Building, No.250, Caoxi Road,Xuhui District , Shanghai 200235
P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com