

**SX-5287-22****Highly Refined Naphthenic Oil for Freezer Compressors****Description**

Group of naphthenic oils for freezer compressors which use freon, ammoniac or carbon dioxide. They also possess excellent lubrication properties when used on industrial equipment.

**Recommended uses**

Similar to lubricant oils for all types of industrial equipment requiring oils with very low pour points. Basically compressors of freezing equipment which use freon, ammoniac or CO<sub>2</sub>.

**Qualities**

Similar to lubricant oils for all types of industrial equipment requiring oils with very low freezing points.

Has a naturally low freezing point, without any additives.

High oxidation resistance thanks to its natural suppressant content.

High chemical stability.

Minimum carbon formation.

Low flocculation point.

**Quality level**

DIN 51503 KC

ISO 6743-3B-DRA

**Technical characteristics**

| Items                 | Unit              | Value                           |
|-----------------------|-------------------|---------------------------------|
| Appearance            | /                 | Light yellow transparent liquid |
| Density at 20°C       | g/cm <sup>3</sup> | 0.901                           |
| Viscosity at 40°C     | cSt               | 23.20                           |
| Viscosity at 100°C    | cSt               | 3.77                            |
| Viscosity Index       |                   | -7                              |
| Flash point, open cup | °C                | 174                             |
| Fire point            | °C                | 192                             |

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai 200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: [www.pingyiao.com](http://www.pingyiao.com)

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)

|                             |    |     |
|-----------------------------|----|-----|
| Pour point                  | °C | -45 |
| Copper Corrosion, 3h, 100°C | /  | 1   |

**Available in**

185 Kg. Drums

**Hazard identification**

These products are not classified as toxic or hazardous according to current legislation.

**Handling**

Minimum safety precautions should be taken when using these products to avoid prolonged contact with the skin and in accordance with good industrial hygiene practices. The use of gloves, visors or glasses is recommended to avoid splashes.

**Health and safety risks**

Inhalation: As this product has low volatility, the risk of inhalation is minimal.  
Ingestion: Do not make an affected person vomit. Supply water. Get medical help.  
Contact with the skin: Wash thoroughly with soap and water. Eyes: Wash thoroughly with water. General measures: Get medical help.

**Fire-fighting measures**

No special measures required. Extinction: Foams, dry chemicals, CO<sub>2</sub>, water spray. Do not apply a jet of water directly, as it could spread the product.

**Environmental precautions**

Danger of physical pollution if spilt (water, coastlines, soil, etc.) due to its floatability and oily consistency that may harm flora and fauna on contact. Prevent the material from entering the water supply. Decontamination and cleaning: Treat as an accidental oil spillage. Avoid dispersion using mechanical barriers and remove with physical or chemical elements.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai 200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: [www.pingyiao.com](http://www.pingyiao.com)

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)