## SX-7279-46

Alkylbenzene refrigeration lubricant

## PRODUCT DESCRIPTION

SX-7279-46 is a high quality synthetic alkylbenzene (AB) refrigeration lubricant and is intended for particularly arduous conditions. The lubricant is designed to be used with halogenated refrigerants in both refrigeration and air-conditioning applications. SX-7279-46 is an excellent lubricant for systems using R-600a, R-22, R-123 and R-502. This oil may also be used where high refrigerant lubricant solubility is required. SX-7279-46 may be recommended for use in piston compressor refrigeration systems. Some advantages of using the SX-7279-46 over the traditional mineral oils are:

- Better Oil Return
- Superior Chemical and Thermal Stability
- Better System Efficiency
- Lower Foaming Tendency
- Lower Floc Point
- Excellent Miscibility Superior Cleanliness

## Typical Physical Properties\*

| Appearance                                    | Light Yellow clear liquid |
|---|---------------------------|
| Density, $20^{\circ}$ C, g/cm <sup>3</sup>    | 0. 864                    |
| Kinematic Viscosity@40°C, $mm^2/s$            | 44.6                      |
| Kinematic Viscosity@100°C, mm <sup>2</sup> /s | 5. 23                     |
| Viscosity Index                               | -1                        |
| Pour Point, °C                                | -33                       |
| Copper Corrosion, 100°C, 3h                   | 1                         |
| Flash Point, Open Cup, °C                     | 184                       |
| Fire Point, °C                                | 202                       |
| Foaming, 24°C                                 | 15/0                      |

\*The above data is typical data, not as product specifications.

Shanghai PingYiao Trading CO., Ltd.Tel: 86-21-64705533Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District , Shanghai 200235P.R.ChinaTelephone helpline: (86)15900706965Fax: 86-21-64705533-209Website: www.pingyiao.comE-mail: info@pingyiao.com