

## SX-9936-150 PAG Synthetic Refrigeration Compressor Oil

SX-9936-150 is unique co-polymers of polyalkylene glycols (PAG). The synthetic base oil ensures good cold flow properties, a high chemical stability and low tendency to evaporation. Primary benefits include:

- Low maintenance costs due to extended oil change intervals and reduced oil consumption
- High efficiency of the refrigerating plants
- Low operating costs due to long service life of filters and oil separators

This high-performance lubricant is recommended for use in:

- Automotive Air Conditioning Applications

### Typical Physical Properties\*

Appearance	Colorless transparent liquid
Density@20°C, g/cm <sup>3</sup>	1.040
Viscosity@40°C, mm <sup>2</sup> /s	149.1
Viscosity@100°C, mm <sup>2</sup> /s	27.77
Viscosity Index	225
Flash Point(open cup), °C	248
Fire Point, °C	268
Pour Point, °C	-42
Copper Strip Test, 100°C, 3hr	1
Foaming, 24°C	30/0

\*The above data is typical data, not as product specifications.

Shanghai PingYiao Trading CO., Ltd.

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai 200235  
P.R.China

Telephone helpline: (86)15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)