

SX-6398-10

Polyol Ester Refrigeration Compressor Fluid

Description

SX-6398-10 is proprietary blend of premium Polyol Ester technology base fluid and additives. This lubricant is formulated to provide superior protection for HFC refrigeration systems. SX-6398-10 offers exceptional solubility and superior lubricity in HFC and Blended Refrigerants.

SX-6398-10 has exceptional chemical and thermal stability, and offers a very long service life.

Benefits

- Excellent low temperature fluidity
- Optimized solubility
- Excellent film strength and anti-wear properties
- Very high flash point for added safety
- Enhanced carbon and varnish control to help reduce deposits
- Very low volatility
- Excellent corrosion and rust control
- Enhanced resistance against water contamination

Typical Properties

Appearance	Colorless transparent liquid
Density@20°C , g/cm ³	0.928
Viscosity(cSt)@40°C	9.50
Viscosity(cSt)@100°C	2.62
Viscosity Index	110
Flash Point °C	200
Fire Point °C	220
Pour Point °C	-69
Copper Corrosion, 3hr	1

* The above data is typical data, not as product specifications.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yinhai Building, No.250, Caoxi Road,Xuhui District , Shanghai 200235
P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com