

SX-6398-120

Polyol Ester Refrigeration Compressor Fluid

Description

SX-6398-120 is proprietary blend of premium Polyol Ester technology base fluid and additives. This lubricant is formulated to provide superior protection for HFC refrigeration systems. SX-6398-120 offers exceptional solubility and superior lubricity in HFC and Blended Refrigerants.

SX-6398-120 has exceptional chemical and thermal stability, and offers a very long service life.

Benefits

- Excellent low temperature fluidity
- Optimized solubility
- Excellent film strength and anti-wear properties
- Very high flash point for added safety
- Enhanced carbon and varnish control to help reduce deposits
- Very low volatility
- Excellent corrosion and rust control
- Enhanced resistance against water contamination

Typical Properties

Appearance	Light yellow transparent liquid
Density@20°C, g/cm ³	0.977
Viscosity(cSt)@40°C	131.2
Viscosity(cSt)@100°C	13.34
Viscosity Index	96
Flash Point °C	290
Fire Point °C	314
Pour Point °C	-36
Copper Corrosion, 3hr	1
Foam Characteristic, 24°C	20/0

* The above data is typical data, not as product specifications.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai 200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com