

ArChine Drawtek SS 145

ArChine Drawtek SS 145 is a medium viscosity, chlorinated, heavy duty forming fluid. It is a blend of high performance extreme pressure and lubricity additives additives.

Application

ArChine Drawtek SS 145 is specially formulated for use in heavy duty deep drawing applications where extreme performance is required.

It is suitable for use on medium to heavy gauge steels, stainless steel, and nickel alloy steels, as well as aluminium and aluminium alloys.

ArChine Drawtek SS 145 is also recommended for use in stainless steel and alloy steel tube cold pilgering operations, where it is applied as an outer diameter roll lubricant, as well as machine gear box lubricant.

Advantages

Contains high performance, extreme pressure additives, which provide very high resistance to temperature and pressure, and high resistance to wear. Enhanced tool and die life, cuts downtime and reduces tooling costs.

Excellent lubricant.

Superior adhesion and wetting performance

TYPICAL PROPERTIES

	ArChine Drawtek SS 145
Viscosity: cSt.@40°C	145

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com