

Shanghai PingYiao Trading CO., Ltd.

Archine Syncolube PE-270

HP-LDPE Compressor Lubricants

Product Description

Archine Syncolube PE-270 has been especially designed to provide the utmost in performance and reliability in the tough service experienced in reciprocating hyper-compressors and intensifiers used in the high-pressure/low-density polyethylene (HP-LDPE) process. These high-performance synthetic PAG lubricants are made from a specially selected polyalkylene glycol-base stock polymer to provide exceptional lubricity and other performance features. A dedicated production facility ensures consistent, high-purity product.,and the product is acceptable under this regulation for use as a lubricant for machinery for producing, manufacturing, packing, processing, preparing, treating, packaging, transporting.

Special Features

- · Cleanliness: no sludge, varnish, lacquer, etc., formed.
- High viscosity index.
- No thickeners added to boost viscosity
- Low pressure-viscosity coefficient.
- Excellent inherent lubricity without use of external lubricity additives.
- Oxidative and thermal stability

Performance Benefits

• Reduced maintenance and substantial maintenance dollar savings resulting from clean-running equipment.

• Increased equipment reliability, allowing scheduled maintenance at predictable intervals. Helps cut down lost production due to unscheduled, random maintenance shut-downs.

• Compressor packings run cooler and longer due to superior lubricity of **Archine Syncolube PE-270** Compressor Lubricant, an inherent property of the base polyalkylene glycol (PAG). There is no need for lubricity additives that are necessary with competitive white oil and polybutene products. Eliminates worries about potential negative effects of lubricity additives on the polyethylene product.

• Archine Syncolube PE-270 Compressor Lubricant contain no polyisobutylene or other thickeners that could drop out and cause deposits on discharge valves.Valves run cleaner and require less maintenance.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.Tel: 86-21-64705533Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250Telephone helpline: (86)15900706965Website: www.pingyiao.comE-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

• Cost-effective lubricant for high-pressure ethylene compressors.

• Low pressure-viscosity co-efficient reduces the lubricator pump pressure necessary to deliver lubricant to the cylinder.

Typical Physical Properties

	Archine Syncolube PE-270	
Viscosity cSt, 40°C	270	
Viscosity Index	195	
Pour Point [°] C	-6	×
Density, g / ml at 20 °C	1.096	$\overline{\mathbf{V}}$
Composition	PAG	
·		7

Changeover Procedure

Anytime a lubricant change is made, care should be taken to assure that the system is properly prepared according to good operating standards. At a minimum, we recommend that old lubricant be drained from the lubricator pumps, the system cleaned, any seals and elastomers inspected, and filters replaced or screens cleaned before the **Archine Syncolube PE-270** Compressor Lubricant is installed. System cleaning may be necessitated by the build-up of sludge and/or varnish in old systems. Physical wiping or flushing with **Archine Syncolube PE-270** Compressor Lubricant may be required if residual contamination is expected. New units require the removal of preservative or coating fluids in similar fashion. After installing the **Archine Syncolube PE-270** Compressor Lubricants to deliver the manufacturer's recommended rate of lubricant. Check filters or screens requently during the early stages of operation since **Archine Syncolube PE-270** Compressor Lubricant will likely loosen residual sludge, varnish, and paint.

Related Key Words :

Archine Syncolube PE-270 Synthetic Hydrocarbon Gas Compressor Oil Archine Syncolube PE-270 Compressor Lubricant, Archine Syncolube PE-270 Compressor Lubricant, Archine Syncolube PE-270F Synthetic Hydrocarbon Gas Compressor Oil Archine Syncolube PE-270F Compressor Lubricant, Archine Syncolube PE-270F Compressor Lubricant, Archine Syncolube PE-270F Compressor Oil Archine Syncolube PE-270L Synthetic Hydrocarbon Gas Compressor Oil Archine Syncolube PE-270L Compressor Lubricant, Archine Synthetic Hydrocarbon Gas Compressor Oil , ArChine Synfluid LDPE-320F, 20000-40000

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.Tel: 86-21-64705533Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250Telephone helpline: (86)15900706965Website: www.pingyiao.comE-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

Oil life, Synthetic Polyalkylene Glycol (PAG) base Compressor Lubricants, HP-LDPE Gas Compressor Lubricant, Pressure up to 3500 bars, ArChine Synfluid LDPE-320L, High Pressure Low Density Polyethylene Gas Compressor Oil, ArChine Syntrend CL 1400SP, copolymer of ethylene with other monomers, vinyl acetate monmer, VAM up to 15%, much less soluble in ethylene than the formulation of PIB/ White oil, WITCO, Polyisobutene and white Oil, ArChine HP-LDPE Gas Compressor Lubricant, High speed Reciprocating Hyper Compressor, Extremely high pressure compression process, Autoclave and Tubular plant, Hyper Compressor, booster, ArChine Syntrend CL 1400, Synthetic PAG base LDPE Gas compressor Lubricant, Extremely high pressure booster, ArChine Syntrend CL 1400SP, copolymer of ethylene with other monomers, vinyl acetate monmer, VAM up to 15%, PAG base Synthetic Hydrocarbon Gas Compressor Oil, ArChine Syntrend CL 1300, Low Winter Temperature, Sulzer Burckhardt HP-LDPE Compressor Oil, ArChine Syntrend CL 1400L, Nuovo Pignone Hyper Compressor Lubricant, Ingersoll-Rand HP-LDPE Compressor, UCON Compressor Lubricants PE-320, IR, High Pressure Low Density Polyethylene Gas Compressor Lubricants & UCON Compressor Lubricants PE-320L, high speed Reciprocating hyper oil . compressor, Extremely high pressure and high speed reciprocating compressor and booster, Breox CL 1400, Dresser-Rand and Clark, Breox CL 1400L, HP-LDPE compressor Oil, Breox CL 1400SP, Synthetic Compressor Lubricants, copolymer of ethylene with other monomers, vinyl acetate monomer, Piston type com[pressor, HITACH HP-LDPE compressor Lubricant Breox CL 1300, ethylene Gas Compressor oil, Witco PIB/White oil formulation, Polyisobutene and white oil formulation, WITCO, HP-LDPE compressor lubricant, Extremely high pressure compression process,

ant te

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.Tel: 86-21-64705533Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250Telephone helpline: (86)15900706965Telephone helpline: (86)15900706965Fax: 86-21-64705533-209Website: www.pingyiao.comE-mail: info@pingyiao.com