

ArChine Geartek SP 320**Product Description:**

ArChine Geartek SP 320 is formulated from high quality high VI base oils combined with selected additives to provide resistance to foaming, rusting, corrosion and oxidation. A sulfur-phosphorus additive is used to give this oil its extreme pressure characteristics which permit industrial gears to withstand heavy loads and shock loading. Unique additive package employed in industrial EP Gear Oil is non-corrosive to brass, bronze, steel or other alloys.

Features:

- * Truly multi-purpose product- wide range of applications
- * Excellent EP and antiwear properties.
- * Compatible with steel, bronze, copper and copper alloys.
- * Superior thermal stability for longer service life.

Typical Uses:

- 1、 **ArChine Geartek SP 320**---- Used in bevel, spur, herringbone, planetary, worm and industrial hypoid gears.
- 2、 **ArChine Geartek SP 320**----- Also used in chain drives, sprockets, plain and anti- friction bearings, slide guides and lexible couplings.
- 3、 **ArChine Geartek SP 320**----- Recommended for use in manual transmissions, gear cases and worm gears on mobile contractor type equipment.

Typical Specications:

	150	320	460
Gravity, °API	27.0	25.2	24.6
Flash Point, °F	450	460	480

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com

ARCHINE

Shanghai PingYiao Trading CO., Ltd.

Fire Point, °F	495	500	510
Viscosity:cSt.@40°C	150	320	460
cSt.@100°C	14.5	23.4	29.6
Viscosity Index	95	92	92
Color, D-1500	4.5	4.5	4.5

Shanghai PingYiao Trading CO., Ltd.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com