

ArChine Hydrotek HLP 46**Product Description:**

ArChine Hydrotek HLP 46 is manufactured from highly refined paraffinic base oils and is fortified with an inhibitor system to provide a product which insures maximum performance in all aspects of hydraulic service. Antiwear agents keep wear rates low on critical pump parts and rust and corrosion problems are eliminated by the rust inhibitor. A foam suppression additive eliminates concerns over operating problems due to foam buildup in the hydraulic storage tank even in high circulation rate systems with low residence times.

Features:

- * High resistance to oxidation gives long oil service life and reduced maintenance expenses due to less frequent oil changes.
- * Excellent air-line oil with minimum stray mist.
- * Highly machined surfaces of hydraulic system components are protected from rust and corrosion.
- * Foam inhibition prevents formation of excessive amounts of foam and reduces the danger of pump failure due to cavitation.
- * Excellent demulsibility means any water present separates from the oil quickly allowing the water to settle out and be drained from the system.
- * A versatile product which can be widely used in many different industrial applications to reduce inventory, prevent equipment damage due to use of the wrong oil and reduce overall maintenance costs.

Typical Uses:

- * **ArChine Hydrotek HLP 46**-----Recommended for all hydraulic systems regardless of the operating pressure.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com

- * **ArChine Hydrotek HLP 46**-----Recommended for all hydraulic pump designs including vane, gear, and axial and radial piston pumps.
- * **ArChine Hydrotek HLP 46**-----Widely used in machine tools, presses, die casting machines, circulating systems and hydraulic control systems.
- * **ArChine Hydrotek HLP 46**-----Used in lubrication of plain and anti-friction bearings, airline lubricators, reciprocating air compressors, moderately loaded gear sets.

Typical Specifications:

	32	46	68
Gravity °API	31.8	31.0	30.3
Flash Point, °F	375	395	425
Fire Point, °F	420	440	470
Pour Point, °F	-20	-20	-5
Viscosity: cSt.@40°C	32	46	68
cSt.@100°C	5.36	6.74	8.62
Viscosity Index	99	99	97
Color, D-1500	2.0	2.0	2.5
Zinc, Wt. %	0.04	0.04	0.04
Phosphorus Wt. %	0.04	0.04	0.04

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com