

ArChine Alumcut HP

ArChine Alumcut HP is a water-miscible EP-coolant based on amine and boron acid for machining operations.

Application

ArChine Alumcut HP is an EP-coolant suitable for machining of aluminium alloys, for demanding operations on steel, cast iron and non ferrous metals.

ArChine Alumcut HP emulsions feature a long time stability even under hot and humid weather conditions, contaminated mixing water and adverse machine surroundings.

Properties

semi-transparent, finely dispersed emulsion

very low foaming

excellent flushing effect

special long-term stability, good sump life

reliable long-time corrosion protection

good skin tolerance

pleasant smell

water hazardous class 1

Technical Data

Concentrate		Emulsion	
viscosity 20 °C (mm ² /s)	mineral oil content %	pH-value fresh preparation at 5 %	Corrosion protection (DIN 51360/1)
approx. 160	approx. 18	9.4	4% grade 0

Remarks

To prepare operating emulsion slowly add the coolant concentrate to drinking quality water assuring thorough mixing. Mixing can also be done by means of an automatic mixer. Recommended mixing ratios:

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com

Machining of steel and non ferrous metals: from 4 %

Machining of cast iron and high tensile steel: from 5 %

Machining of aluminium alloys: from 5 %

The concentration of the operating emulsion can be determined by means of a pocket refractometer. The °Brix value multiplied by the refractometer value equals the concentration in %. Sometimes reading of scale is more difficult with older emulsions because of the more coarse dispersivity.

Refractometer factor 1,00

ArChine Alumcut HP coolants are free of chlorinated organic substances, nitrite and secondary amines. This product contains natural raw materials. Therefore, different shades of colour and appearance are possible, however, quality and function of the product are not affected at all.

Subject to modification of the technical data. Please refer to the material safety data sheet for additional information or contact our application engineers.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com