

Shanghai PingYiao Trading CO., Ltd.

ArChine Screwtech EMG 39

8000 hours Synthetic Compressor Oil

Product Description

ArChine Screwtech EMG 39 is developed from an unique of PAG and POE, which together form an exceptional coolant and act to reduce deposit formation. ArChine Screwtech EMG 39 enables high load-carrying capability, enhancing the overall compressor productivity and equipment life. The lubricant also provides effective rust and corrosion protection. It is long life lubricant and has more than 8000 hours service life.

Features and Benefits

- Fully 100% synthetic
- Wide temperature range
- Cost effective: Extended oil change intervals
- Eliminates deposit formation
- High flash point mean reduced fire hazards
- Excellent oxidative and thermal stability
- Biodegradable

Applications

ArChine Screwtech EMG 39 can be recommended for use in rotary screw compressors and heavy duty industrial applications.

Typical Properties*

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

ArChine Screwtech EMG 39	Typical Value
Appearance	light yellow transparent liquid
Density@ 20°C, g/cm ³	0.974
Viscosity@ 40°C, mm ² /s	37.1
Viscosity@ 100°C, mm ² /s	7.12
Viscosity Index	158
Flash Point, °C (open cup)	252
Fire point, °C	274
Pour Point, °C	-48
Foaming Characteristics 24°C,	20/0
Copper Strip Corrosion, 100°C/3hr, grade	100

^{*}Typical data shall not be used as product specifications.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com