

ArChine Refritech TPE 32

Polyol Ester Refrigeration Compressor Fluid

Description

ArChine Refritech TPE 32 is proprietary blend of premium Polyol Ester technology base fluid and small part of synthetic base fluid to optimize the miscibility. And the special additives package to upgrade the performance.. This lubricant is formulated to provide superior protection for HFC refrigeration systems. ArChine Refritech TPE 32 offers exceptional solubility and superior lubricity in HFC and Blended Refrigerants. ArChine Refritech TPE 32 has exceptional chemical and thermal stability, and offers a very long service life.

Benefits

- Excellent low temperature fluidity
- Optimized solubility
- Excellent film strength and anti-wear properties
- Very high flash point for added safety
- Enhanced carbon and varnish control to help reduce deposits
- Very low volatility
- Excellent corrosion and rust control
- Enhanced resistance against water contamination

Typical Properties

ArChine Refritech TPE	ISO 32
Appearance	Light yellow transparent liquid
Density@ 20°C, g/cm ³	0.940
Viscosity (cSt) @ 40°C	29.2
Viscosity (cSt) @ 100°C	4.73
Flash Point °C	196
Fire Point °C	212
Pour Point °C	-51
Copper Corrosion, 3 hr	1

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com

ARCHINE

Shanghai PingYiao Trading CO., Ltd.

* The above data is typical data, not as product specifications.

Shanghai PingYiao Trading CO., Ltd.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com