

Shanghai PingYiao Trading CO., Ltd.

ArChine Gascomp GHT 100

Semi-Synthetic Hydrocarbon Gas Compressor Oil

ArChine Gascomp GHT 100 is custom-blended, highly refined, semi-synthetic lubricant. This product provides excellent wear protection as well as enhanced resistance against oxidation, rust, corrosion and carbon buildup.

Features

- Excellent oxidation stability
- High film strength
- Reduced downtime and maintenance costs
- Outstanding fluid life
- Reduced lubricant consumption

Application:

Crading CO ArChine Gascomp GHT 100 is widely used for applications where lubricants give negligible solubility in contact with hydrocarbon gas. It is also recommended for use in harsh chemical environments and sour hydrocarbon (H2S) gas systems.

Typical Physical Properties*

Properties	ArChine Gascomp GHT 100
Appearance	Light yellow, clear liquid
Density, 20°C g/cm3	0.869
Viscosity@ 40°C, mm ² /s	105.9
Viscosity@100°C, mm²/s	11.72
Viscosity Index	98
Flash Point(open cup), °C	248
Fire Point, °C	270
Pour Point, °C	-21

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

Copper Strip Test, 100℃, 3hr

1

Shanghai Ping Yiao Trading CO.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com

^{*}The above data is typical data, not as product specifications.