

Shanghai PingYiao Trading CO., Ltd.

ArChine Gascomp GHT 460

Semi-Synthetic Hydrocarbon Gas Compressor Oil

ArChine Gascomp GHT 460 is custom-blended, highly refined, semi-synthetic lubricant. This product provides excellent wear protection as well as enhanced resistance against oxidation, rust, corrosion and carbon buildup.

Features

- Excellent oxidation stability
- High film strength
- Reduced downtime and maintenance costs
- Outstanding fluid life
- Reduced lubricant consumption

Application:

Trading CO ArChine Gascomp GHT 460 is widely used for applications where lubricants give negligible solubility in contact with hydrocarbon gas. It is also recommended for use in harsh chemical environments and sour hydrocarbon (H2S) gas systems.

Typical Physical Properties*

| Properties | ArChine Gascomp GHT 460 |
|--------------------------|----------------------------|
| Appearance | Light yellow, clear liquid |
| Density, 20°C g/cm3 | 0.877 |
| Viscosity@ 40°C, mm²/s | 468.6 |
| Viscosity@100°C, mm²/s | 32.06 |
| Viscosity Index | 100 |
| Flash Point(open cup), ℃ | 246 |
| Fire Point, °C | 268 |
| Pour Point, °C | -21 |

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

Copper Strip Test, 100℃, 3hr

1

Shanghai Ping Yiao Trading CO.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com

^{*}The above data is typical data, not as product specifications.