

ArChine Gascomp GHT 68

Semi-Synthetic Hydrocarbon Gas Compressor Oil

ArChine Gascomp GHT 68 is custom-blended, highly refined, semi-synthetic lubricant. This product provides excellent wear protection as well as enhanced resistance against oxidation, rust, corrosion and carbon buildup.

Features

- Excellent oxidation stability
- High film strength
- Reduced downtime and maintenance costs
- Outstanding fluid life
- Reduced lubricant consumption

Application:

ArChine Gascomp GHT 68 is widely used for applications where lubricants give negligible solubility in contact with hydrocarbon gas. It is also recommended for use in harsh chemical environments and sour hydrocarbon (H₂S) gas systems.

Typical Physical Properties*

Properties	ArChine Gascomp GHT 68
Appearance	Light yellow, clear liquid
Density, 20°C g/cm ³	0.866
Viscosity@ 40°C, mm ² /s	67.1
Viscosity@100°C, mm ² /s	8.62
Viscosity Index	99
Flash Point(open cup), °C	236
Fire Point, °C	258
Pour Point, °C	-18

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com

ARCHINE

Shanghai PingYiao Trading CO., Ltd.

Copper Strip Test, 100°C, 3hr	1
-------------------------------	---

*The above data is typical data, not as product specifications.

Shanghai PingYiao Trading CO., Ltd.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com