

**ArChine Gascomp HGS 220****Water soluble Hydrocarbon Gas Compressor Oil**

ArChine Gascomp HGS 220 is unique co-polymers of polyalkylene glycols (PAG). Primary benefits include:

- Thermal stability
- Insoluble in hydrocarbon gas
- Resist dilution for stable viscosity
- Water soluble

This high-performance lubricant is recommended for use in:

- Liquid ring vacuum pumps
- Centrifugal compressors
- Flooded rotary screw compressors

**Typical Physical Properties\***

Properties	ArChine Gascomp HGS 220
Appearance	Light yellow, clear liquid
Density@20°C, g/cm <sup>3</sup>	1.041
Viscosity@ 40°C, mm <sup>2</sup> /s	217.4
Viscosity@ 100°C, mm <sup>2</sup> /s	37.98
Viscosity Index	227
Flash Point(open cup), °C	286
Fire Point, °C	308
Pour Point, °C	-39
Copper Strip Test, 100°C, 3hr	1
Foaming, 24°C	15/0

\*The above data is typical data, not as product specifications.

**Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai  
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: [www.pingyiao.com](http://www.pingyiao.com)

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)