

ArChine Gascomp HGS 32**Water soluble Hydrocarbon Gas Compressor Oil**

ArChine Gascomp HGS 32 is unique co-polymers of polyalkylene glycols (PAG).

Primary benefits include:

- Thermal stability
- Insoluble in hydrocarbon gas
- Resist dilution for stable viscosity
- Water soluble

This high-performance lubricant is recommended for use in:

- Liquid ring vacuum pumps
- Centrifugal compressors
- Flooded rotary screw compressors

Typical Physical Properties*

Properties	ArChine Gascomp HGS 32
Appearance	Light yellow, clear liquid
Density@20°C, g/cm ³	1.022
Viscosity@ 40°C, mm ² /s	32.4
Viscosity@ 100°C, mm ² /s	6.99
Viscosity Index	185
Flash Point(open cup), °C	212
Fire Point, °C	232
Pour Point, °C	-54
Copper Strip Test, 100°C, 3hr	1
Foaming, 24°C	10/0

*The above data is typical data, not as product specifications.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com