

**ArChine Gascomp HGS 68****Water soluble Hydrocarbon Gas Compressor Oil**

ArChine Gascomp HGS 68 is unique co-polymers of polyalkylene glycols (PAG).

Primary benefits include:

- Thermal stability
- Insoluble in hydrocarbon gas
- Resist dilution for stable viscosity
- Water soluble

This high-performance lubricant is recommended for use in:

- Liquid ring vacuum pumps
- Centrifugal compressors
- Flooded rotary screw compressors

**Typical Physical Properties\***

Properties	Standard	ArChine Gascomp HGS 68
Appearance	Visual	Light yellow, clear liquid
Density@20°C, g/cm <sup>3</sup>	ISO 3675	1.031
Viscosity@ 40°C, mm <sup>2</sup> /s	ASTM D445	68.8
Viscosity@100°C, mm <sup>2</sup> /s	ASTM D445	13.40
Viscosity Index	ASTM D2270	201
Flash Point(open cup), °C	ASTM D92	284
Fire Point, °C	ASTM D92	302
Pour Point, °C	ASTM D97	-45
Copper Strip Test, 100°C, 3hr	ASTM D130	1

\*The above data is typical data, not as product specifications.

**Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai  
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: [www.pingyiao.com](http://www.pingyiao.com)

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)