

ArChine Gascomp PAO 220**Synthetic PAO Hydrocarbon Gas Compressor Oil**

ArChine Gascomp PAO 220 is long life lubricant formulated with high quality polyalphaolefin (PAO) base oil and rust and oxidation inhibitors. It gives improved lubrication at high and low temperatures, negligible solubility or dilution in contact with hydrocarbon gas, and is compatible with mineral oils. Primary benefits include:

- Excellent thermal stability
- Very low volatility
- Resist dilution for stable viscosity
- Outstanding fluidity at low temperature

This high-performance lubricant is recommended for use in:

- Hydrocarbon gas compressors
- Flooded rotary screw compressors

Typical Physical Properties*

Properties	ArChine Gascomp PAO 220
Appearance	Light yellow, clear liquid
Density@20°C, g/cm ³	0.847
Viscosity@ 40°C, mm ² /s	214.6
Viscosity@100°C, mm ² /s	24.74
Viscosity Index	145
Flash Point(open cup), °C	272
Fire Point, °C	296
Pour Point, °C	-42
Copper Strip Test, 100°C, 3hr	1

*The above data is typical data, not as product specifications.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com