

**ArChine Gascomp PAO 320****Synthetic PAO Hydrocarbon Gas Compressor Oil**

ArChine Gascomp PAO 320 is long life lubricant formulated with high quality polyalphaolefin (PAO) base oil and rust and oxidation inhibitors. It gives improved lubrication at high and low temperatures, negligible solubility or dilution in contact with hydrocarbon gas, and is compatible with mineral oils. Primary benefits include:

- Excellent thermal stability
- Very low volatility
- Resist dilution for stable viscosity
- Outstanding fluidity at low temperature

This high-performance lubricant is recommended for use in:

- Hydrocarbon gas compressors
- Flooded rotary screw compressors

**Typical Physical Properties\***

Properties	ArChine Gascomp PAO 320
Appearance	Light yellow, clear liquid
Density@20°C, g/cm <sup>3</sup>	0.849
Viscosity@ 40°C, mm <sup>2</sup> /s	320.6
Viscosity@100°C, mm <sup>2</sup> /s	33.68
Viscosity Index	148
Flash Point(open cup), °C	276
Fire Point, °C	298
Pour Point, °C	-39
Copper Strip Test, 100°C, 3hr	1

\*The above data is typical data, not as product specifications.

**Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai  
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: [www.pingyiao.com](http://www.pingyiao.com)

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)