

ArChine Gascomp WSG 220

Water soluble Hydrocarbon Gas Compressor Oil

ArChine Gascomp WSG 220 is polyalkylene glycol lubricant, formulated to give negligible solubility or dilution in contact with hydrocarbon liquids or vapors.

Primary benefits include:

- Thermal stability
- Insoluble in hydrocarbon gas
- Resist dilution for stable viscosity
- Water soluble

This high-performance lubricant is recommended for use in:

- Liquid ring vacuum pumps
- Centrifugal compressors
- Flooded rotary screw compressors

Typical Physical Properties*

Properties	ArChine Gascomp WSG 220
Appearance	Light yellow, clear liquid
Density, 20°C g/cm ³	1.047
Viscosity@ 40°C, mm ² /s	222.8
Viscosity@100°C, mm ² /s	40.46
Viscosity Index	236
Flash Point(open cup), °C	260
Fire Point, °C	278
Pour Point, °C	-21
Copper Strip Test, 100°C, 3hr	1
Foaming, 24°C	10/0

*The above data is typical data, not as product specifications.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com