

ArChine Refritech QPE 120 (POE 120)

ArChine Refritech QPE 120 (POE 120) is designed for standard factory fill of air conditioning and industrial refrigeration equipment, as well as for OEM retrofitting operations. It provides improved properties over conventional mineral oils in all aspects, including viscosity index, flash and fire points, and pour point.

Through this effort, we've been able to identify lubricants that meet a compressor's specific requirements and needs.

ArChine Refritech QPE	ISO 120
Appearance	Light yellow transparent liquid
Density@ 20°C, g/cm ³	0.966
Viscosity (cSt) @ 40°C	113.60
Viscosity (cSt) @ 100°C	12.40
Viscosity Index	100
Flash Point °C	282
Fire Point °C	308
Pour Point °C	-36
Copper Corrosion, 3 hr	1
Foam Characteristic, 24°C	15/0

* The above data is typical data, not as product specifications.ies.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yinhai Building, No.250, Caoxi Road,Xuhui District , Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com