



BOTE MoS2 HPG-2

Description:

Multi-purpose E.P. Grease is a high-quality, lithium soap grease that contains an optimum percentage of solid lubricants, including MoS₂, in combination with other highly effective extreme-pressure additives.

Feature:

universal application
cold- and hot-water resistant
distinctive high-pressure characteristics for high load-carry capacity
stable to ageing and milling
reliable corrosion protection
reduces friction and wear
cost effective due to high operational safety
extremely long lubricity
can be delivered by centralized lubrication systems

Applications:

For general use under extreme conditions. For the assembly ,maintenance and repair of motor vehicles, machine tools, construction machinery and presses. For high-load bearings and joints, splined shafts, threads and guides. Suitable for constant velocity joints.

Technical Data:

Colour	Dark grey
Based on	Mineral oil
Thickener	Lithium soap
MoS ₂ Content	2.0 wt %
NLGI class	2
Worked penetration	290
Drop point	195°C
Operating temperature range	-30°C to +130°C

Shanghai PingYiao Trading Co.,Ltd

Add: No 1210,Yinhai Building,Caoxi Road,Xuhui District, Shanghai

Website: www.pingyiao.com

Tel: 86-21-64705533

24H:86-15900706965

E-mail: info@pingyiao.com

Fax: 86-21-64820538