

CP-1520-460

PRODUCT DESCRIPTION

CP-1520-460 product is fully formulated synthetic gear and bearing lubricants based on a unique co-polymer of polyalkylene glycols. The many advantages include thermal stability, low ash content, high viscosity index, shear stability, low solubility with many hydrocarbons and excellent lubricity.

CP-1520-460 product can often extend tooth life in gears by decreasing or eliminating spalling and reducing pitting and wear. This is particularly true in the case of bronze-on-steel gearing surfaces.

CP-1520-460 product is insoluble with water, and are fortified with rust and oxidation inhibitors. They also contain antiwear and mild boundary lubrication additives.

TYPICAL PROPERTIES*

CP-1520-460

Viscosity @ 40°C cst ASTM D445	465.1
Viscosity @ 100°C cst	70.0
Viscosity @ 100°F, SUS	2362
Viscosity @ 210°F, SUS	335
Viscosity Index ASTM D2270	230
Density, lb/gal, 60°F	8.33
Pour Point °F (°C) ASTM D97	-33 (-36)
Flash Point, C.O.C., °F (°C) ASTM D92	470 (243)
Fire Point, C.O.C., °F (°C) ASTM D92	500 (260)
Specific Gravity, ASTM D1298	1.00

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com