

## **CP-1520-680**

### **PRODUCT DESCRIPTION**

CP-1520-680 product is fully formulated synthetic gear and bearing lubricants based on a unique co-polymer of polyalkylene glycols. The many advantages include thermal stability, low ash content, high viscosity index, shear stability, low solubility with many hydrocarbons and excellent lubricity.

CP-1520-680 product can often extend tooth life in gears by decreasing or eliminating spalling and reducing pitting and wear. This is particularly true in the case of bronze-on-steel gearing surfaces.

CP-1520-680 product is insoluble with water, and are fortified with rust and oxidation inhibitors. They also contain antiwear and mild boundary lubrication additives.

#### **TYPICAL PROPERTIES\***

#### **CP-1520-680**

Viscosity @ 40°C cst ASTM D445	635
Viscosity @ 100°C cst	90.9
Viscosity @ 100°F, SUS	3256
Viscosity @ 210°F, SUS	436
Viscosity Index ASTM D2270	234

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)