

CP-4620-100

Synthetic Gear Lubricants

PRODUCT DESCRIPTION

CP-4620 series products are fully formulated synthetic gear and bearing lubricants based on synthetic hydrocarbons. The CP-4620 series products have excellent thermal and oxidative stability, combined with superior gear load carrying ability.

The synthetic hydrocarbon base fluid has proved in extensive field evaluations to give extended service life and overall economic benefits. Synthetic hydrocarbons combine high viscosity indexes, high film strength and excellent mechanical shear resistance even in heavily loaded gear applications. Additives provide superior oxidative stability corrosion protection and load carrying ability. Field test reports state that lower operating temperatures are possible due to reduction in heat build-up due to friction. The reduced friction may also reduce horsepower requirements up to five percent depending on other operating and environmental conditions.

TYPICAL PROPERTIES*	CP-4620-100
Viscosity@40°C,cSt, ASTM D445	100.3
Viscosity @100°C,cSt	13.7
Viscosity @100°F	111.4
Viscosity @210°F	14.1
Viscosity Index ASTM D2270	138
Density lb/gal, 60°F	6.99
Pour point °F(°C) ASTM D97	-55(-52)
Flash point C.O.C.,°F(°C) ASTM D92	521(271)
Fire point C.O.C.,°F(°C) ASTM D92	574(301)
Specific Gravity, ASTM D1298	0.839

* These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com