## Shanghai PingYiao Trading CO., Ltd.

## **CP-4620-460**

## **Synthetic Gear Lubricants**

## PRODUCT DESCRIPTION

CP-4620 series products are fully formulated synthetic gear and bearing lubricants based on synthetic hydrocarbons. The CP-4620 series products have excellent thermal and oxidative stability, combined with superior gear load carrying ability.

The synthetic hydrocarbon base fluid has proved in extensive field evaluations to give extended service life and overall economic benefits. Synthetic hydrocarbons combine high viscosity indexes, high film strength and excellent mechanical shear resistance even in heavily loaded gear applications. Additives provide superior oxidative stability corrosion protection and load carrying ability. Field test reports state that lower operating temperatures are possible due to reduction in heat build-up due to friction. The reduced friction may also reduce horsepower requirements up to five percent depending on other operating and environmental conditions.

TYPICAL PROPERTIES*	CP-4620-460
Viscosity@40°C,cSt, ASTM D445	392.0
Viscosity @100°C,cSt	38.8
Viscosity @100°F	441.6
Viscosity @210°F	40.0
Viscosity Index ASTM D2270	147
Density 1b/gal, 60°F	7.10
Pour point °F(°C) ASTM D97	-35(-37)
Flash point C.0.C., $^{\circ}F(^{\circ}C)$ ASTM D92	545(285)
Fire point C.0.C., $F(^{\circ}C)$ ASTM D92	595(313)
Specific Gravity, ASTM D1298	0.852

<sup>\*</sup> These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250 Telephone helpline: 15900706965 Fax: 86-21-64705533-209 Website: <a href="https://www.pingyiao.com">www.pingyiao.com</a> E-mail: <a href="mailto:info@pingyiao.com">info@pingyiao.com</a>