

CP-4627-320

The CP-4627 series lubricants are custom-blended, polyalphaolefin (PAO) synthetic hydrocarbon fluids that meet or exceed the following specifications:

U.S. Steel 224

AGMA 9005

DIN 51517 part 3

David Brown S1.52.101

Cincinnati machine

Primary benefits include:

Excellent thermal and oxidative stability

Superior corrosion protection

High mechanical shear resistance

Resistance to micro pitting

Superior gear load-carrying ability

Compatibility with internal coating used in gear boxes

Outstanding gear box bearing lubrication

These high-performance lubricants are recommended for use with industrial gears such as spur gears, helical gears, bevel gears, and planetary gears.

Preliminary product selection guide

Product name	CP-4627-320
Viscosity @40°C cSt ASTM D445	320
Viscosity @100°C cst	33.0
Viscosity @100°F	1678
Viscosity @200°F	161
Viscosity Index ASTM D2270	145

*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com