CP-4627-460

The CP-4627 series lubricants are custom-blended, polyalphaolefin (PAO) synthetic hydrocarbon fluids that meet or exceed the following specifications:

U.S. Steel 224

AGMA 9005

DIN 51517 part 3

David Brown S1.52.101

Cincinnati machine

Primary benefits include:

Excellent thermal and oxidative stability

Superior corrosion protection

High machanical shear resistance

Resistance to micro pitting

Superior gear load-carrrying ability

Compatibility with internal coating used in gear boxes

Outstanding gear box bearing lubrication

These high-performance lubricants are recommended for use with industrial gears such as spur gears, helical gears, bevel gears, and planetary gears.

Preliminary product selection guide

Product name	**CP-4627-460**
Viscosity @40℃ cSt ASTMD445	449
Viscosity @100℃ cst	35.7
Viscosity @100℉	2391
Viscosity @200℉	174
Viscosity Index ASTMD2270	119

*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO.，Ltd. Tel：86-21-64705533
Adress：Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250
Telephone helpline：15900706965 Fax：86-21-64705533-209
Website：www.pingyiao.com E-mail：info@pingyiao.com

Shanghai PingYiao Trading CO., Ltd.