

CP-4637-320

The CP-4637 series lubricants are custom-blended, polyalphaolefin (PAO) synthetic hydrocarbon based gear oil that meet or exceed the following specifications:

U.S. Steel 224

AGMA 9005-E02

DIN 51517 part 3:2004-01

David Brown S1.52.101

Cincinnati machine EP gear oil

Flender approved

ISO 12925-1 CKC/D

Primary benefits include:

Excellent thermal and oxidative stability

Superior gear load-carrying ability

Excellent mechanical shear resistance

Superior corrosion protection

Resistance to micro pitting

Compatibility with internal coating used in gear boxes

These Flender approved high-performance gear oils are recommended for use with industrial gears such as spur gears, helical gears, bevel gears, and planetary gears, including those used in wind turbine application.

Preliminary product selection guide

Product name	CP-4637-320
Viscosity @40°C cSt ASTM D445	331
Viscosity @100°C cst	34.7
Viscosity @100°F	1734
Viscosity @200°F	169

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com



CPI ENGINEERING SERVICES, INC.
Specializing in Synthetic Lubricants

Shanghai PingYiao Trading CO., Ltd.

Viscosity Index ASTMD2270	149
---------------------------	-----

*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com