

CP-4677-320-F

Food Grade Tackified Gear Lubricants

PRODUCT DESCRIPTION

CP-4677-F series products are custom-blended polyalphaolefin (PAO) synthetic hydrocarbon fluids giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

CP-4677-F series products are long life lubricants formulated especially for applications where antiwear and extreme pressure properties are needed for effective load carrying ability. Recommended for gear applications.

CP-4677-F series products are tackified to adhere to metal surfaces, preventing throwing off or dripping. This adhesive/cohesive feature makes it ideal in applications where oil control is necessary such as chain applications and high speed gear applications.

| TYPICAL PROPERTIES* | CP-4677-320-F |
|--------------------------------------|----------------------|
| Viscosity @40°C, cSt, ASTM D445 | 320.0 |
| Viscosity @100°C, cSt | 33.0 |
| Viscosity @100°F | 359.9 |
| Viscosity @210°F | 34.0 |
| Viscosity Index ASTM D2270 | 145 |
| Density , lb/gal, 60°F | 7.08 |
| Pour Point °F (°C)ASTM D97 | -38(-39) |
| Flash Point, C.O.C., °F (°C)ASTM D92 | 540(282) |
| Fire Point, C.O.C., °F (°C)ASTM D92 | 592(311) |
| Specific Gravity, ASTM D1298 | 0.850 |

* These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com