

CP-4677-460-F

Food Grade Tackified Gear Lubricants

PRODUCT DESCRIPTION

CP-4677-F series products are custom-blended polyalphaolefin (PAO) synthetic hydrocarbon fluids giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

CP-4677-F series products are long life lubricants formulated especially for applications where antiwear and extreme pressure properties are needed for effective load carrying ability. Recommended for gear applications.

CP-4677-F series products are tackified to adhere to metal surfaces, preventing throwing off or dripping. This adhesive/cohesive feature makes it ideal in applications where oil control is necessary such as chain applications and high speed gear applications.

TYPICAL PROPERTIES*	CP-4677-460-F
Viscosity @40°C, cSt, ASTM D445	392.0
Viscosity @100°C, cSt	38.8
Viscosity @100°F	441.6
Viscosity @210°F	40.0
Viscosity Index ASTM D2270	147
Density , lb/gal, 60°F	7.10
Pour Point °F (°C)ASTM D97	-35(-37)
Flash Point, C.O.C., °F (°C)ASTM D92	545(285)
Fire Point, C.O.C., °F (°C)ASTM D92	595(313)
Specific Gravity, ASTM D1298	0.852

* These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com