

## **CP-4678-150-F**

### **PRODUCT DESCRIPTION**

CP-4678-F series products are custom-blended polyalphaolefin (PAO) synthetic hydrocarbon oil giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

CP-4678-F series products are tackified to adhere to metal surfaces, prevent throwing off or dripping. This adhesive/cohesive feature makes it ideal in applications where oil control is necessary such as in textile mills and food processing plants.

Complies with FDA 21 CFR 178.3570—Lubricants with Incidental Food Contact.

#### **TYPICAL PROPERTIES\***

#### **CP-4678-150-F**

Viscosity @ 40°C, cSt, ASTM D445	147.7
Viscosity @ 100°C, cSt	18.2
Viscosity @ 100°F	164.8
Viscosity @ 210°F	18.7
Viscosity Index ASTM D2270	140
Density, 1b/gal, 60°F	7.16
Pour Point °F (°C) ASTM D92	-50 (-46)
Flash Point, C.O.C., °F (°C) ASTM D92	510 (265)
Fire Point, C.O.C., °F (°C) ASTM D 92	560 (293)
Specific Gravity, ASTM D1298	0.860

\* These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)