

CP-4678-68-F

PRODUCT DESCRIPTION

CP-4678-F series products are custom-blended polyalphaolefin (PAO) synthetic hydrocarbon oil giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

CP-4678-F series products are tackified to adhere to metal surfaces, prevent throwing off or dripping. This adhesive/cohesive feature makes it ideal in applications where oil control is necessary such as in textile mills and food processing plants.

Complies with FDA 21 CFR 178.3570–Lubricants with Incidental Food Contact.

TYPICAL PROPERTIES*

CP-4678-68-F

| | |
|---------------------------------------|-----------|
| Viscosity @ 40°C, cSt, ASTM D445 | 65.6 |
| Viscosity @ 100°C, cSt | 9.8 |
| Viscosity @ 100°F | 72.5 |
| Viscosity @ 210°F | 10.0 |
| Viscosity Index ASTM D2270 | 132 |
| Density, 1b/gal, 60°F | 6.91 |
| Pour Point °F (°C) ASTM D92 | -65 (-54) |
| Flash Point, C.O.C., °F (°C) ASTM D92 | 525 (274) |
| Fire Point, C.O.C., °F (°C) ASTM D 92 | 570 (299) |
| Specific Gravity, ASTM D1298 | 0.830 |

* These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com